

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

1 Identification

- **Product identifier**
- **Trade name: Parabond DETACH II**
- **Relevant identified uses of the substance or mixture.** Cleaner (Non-Animal Origin)
- **Details of the supplier of the safety data sheet**
- **Company information:**
H.B. Fuller Construction Products Inc.
1105 S. Frontenac Street
Aurora, IL 60504
1-800-552-6225
- **Information department:** Environment protection department.
- **Emergency telephone number:**
ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07

- **Signal word** Danger
- **Hazard statements**
Harmful in contact with skin or if inhaled.
Causes severe skin burns and eye damage.
- **Precautionary statements**
Do not breathe dusts or mists.
Wear protective gloves / protective clothing.
Wear eye protection / face protection.
Wash thoroughly after handling.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 1)

Use only outdoors or in a well-ventilated area.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Immediately call a POISON CENTER/doctor.
 Specific treatment (see on this label).
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Wash contaminated clothing before reuse.
 If swallowed: Rinse mouth. Do NOT induce vomiting.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Cleansing agent

· **Hazardous components:**

111-76-2	ethylene glycol monobutyl ether	25-50%
141-43-5	2-aminoethanol	10-25%
127087-87-0	nonylphenol polyethylene glycol ether	2.5-10%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

· **After eye contact:** Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 2)

- **After swallowing:**
Rinse out mouth with water. Drink 1 - 2 glasses of water but **DO NOT** induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Isolate area. Keep unnecessary and unprotected personnel from entering the area.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Open and handle receptacle with care.
Avoid prolonged or repeated contact with skin.
Avoid contact with eyes.
Wash thoroughly after handling.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Open containers in a well ventilated area and avoid breathing headspace vapors.
- **Information about protection against explosions and fires:** No special measures required.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store above 40F and below 100F.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

111-76-2 ethylene glycol monobutyl ether

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

141-43-5 2-aminoethanol

PEL	Long-term value: 6 mg/m ³ , 3 ppm
REL	Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 8 mg/m ³ , 3 ppm
TLV	Short-term value: 15 mg/m ³ , 6 ppm Long-term value: 7.5 mg/m ³ , 3 ppm

· Ingredients with biological limit values:

111-76-2 ethylene glycol monobutyl ether

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment (see listings below)**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
Not necessary if room is well-ventilated.
Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Butyl rubber, BR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

Face Shield

· **Body protection:**

Protective work clothing

Apron

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value at 20 °C (68 °F):** 12.2

· **Change in condition**

Melting point: Undetermined.

· **Boiling point:** > 100 °C (> 212 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Flammable limits:**

Lower: 1.1 Vol %

Upper: 10.6 Vol %

· **Vapor pressure at 20 °C (68 °F):** 1.2 hPa (1 mm Hg)

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: **Parabond DETACH II**

(Contd. of page 5)

- **Specific gravity at 20 °C (68 °F):** 0.97 g/cm³ (8.095 lbs/gal)
- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with Water:** Not soluble

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**
- **Dynamic:** Not determined.
- **Kinematic:** Not determined.

- **Solvent content:**
- **VOC (Per EPA 24)** not available GMS/L
- **Other information** California VOC Compliance
- Contains Solvent
- SCAQMD Rule 1168: Product is not regulated under this rule.
- SCAQMD Rule 443.1: Grams VOC per Liter of Material <578 grams/liter
- Grams VOC per Liter of Coating <892 grams/liter

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flames, sparks.
- **Incompatible materials:** Strong oxidizers, acids, and bases.
- **Hazardous decomposition products:**
- Carbon monoxide and carbon dioxide
- Nitrogen oxides
- Ammonia
- Ethanol
- Hydrocarbons

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

111-76-2 ethylene glycol monobutyl ether

Oral LD50 1480 mg/kg (rat)

Dermal LD50 400 mg/kg (rab)

141-43-5 2-aminoethanol

Oral LD50 2050 mg/kg (rat)

Dermal LD50 1000 mg/kg (rabbit)

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: **Parabond DETACH II**

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Causes serious eye damage
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

111-76-2	ethylene glycol monobutyl ether	3
111-42-2	diethanolamine	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN2922

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 7)

· **UN proper shipping name**
 · **DOT** Corrosive liquids, toxic, n.o.s. (Ethanolamine, ethylene glycol monobutyl ether)
 · **ADR** 2922 Corrosive liquids, toxic, n.o.s. (Ethanolamine, ethylene glycol monobutyl ether)
 · **IMDG, IATA** CORROSIVE LIQUID, TOXIC, N.O.S. (ETHANOLAMINE, ethylene glycol monobutyl ether)

· **Transport hazard class(es)**· **DOT**

· **Class** 8 Corrosive substances
 · **Label** 8+6.1

· **ADR, IMDG, IATA**

· **Class** 8 Corrosive substances
 · **Label** 8+6.1

· **Packing group**· **DOT, ADR, IMDG, IATA** III· **Environmental hazards:** Not applicable.· **Special precautions for user** Warning: Corrosive substances· **Danger code (Kemler):** 86· **EMS Number:** F-A,S-B· **Segregation groups** Alkalis

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **UN "Model Regulation":** UN2922, Corrosive liquids, toxic, n.o.s. (Ethanolamine, ethylene glycol monobutyl ether), 8 (6.1), III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

111-76-2 ethylene glycol monobutyl ether

111-42-2 diethanolamine

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 8)

· Proposition 65
· Chemicals known to cause cancer:

111-42-2	diethanolamine
----------	----------------

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· (DSL) Canada Domestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· New Jersey Right-to-Know List:

111-76-2	ethylene glycol monobutyl ether
----------	---------------------------------

141-43-5	2-aminoethanol
----------	----------------

· New Jersey Special Hazardous Substance List:

111-76-2	ethylene glycol monobutyl ether	CA, F2
----------	---------------------------------	--------

141-43-5	2-aminoethanol	CO, F2
----------	----------------	--------

· Pennsylvania Right-to-Know List:

111-76-2	ethylene glycol monobutyl ether
----------	---------------------------------

141-43-5	2-aminoethanol
----------	----------------

· Pennsylvania Special Hazardous Substance List:

None of the ingredients is listed.

· Cancerogenity categories
· EPA (Environmental Protection Agency)

111-76-2	ethylene glycol monobutyl ether	NL
----------	---------------------------------	----

· TLV (Threshold Limit Value established by ACGIH)

111-76-2	ethylene glycol monobutyl ether	A3
----------	---------------------------------	----

111-42-2	diethanolamine	A3
----------	----------------	----

· MAK (German Maximum Workplace Concentration)

111-76-2	ethylene glycol monobutyl ether	4
----------	---------------------------------	---

111-42-2	diethanolamine	3B
----------	----------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, H.B. Fuller Construction Products Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will H.B. Fuller Construction Products Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/27/2016

Revision Number 2

Revision Date 02/27/2016

Trade name: Parabond DETACH II

(Contd. of page 9)

· **Department issuing SDS:** Environment protection department.

· **Creation Date:** 12/23/2013

· **Date of preparation / last revision** 02/27/2016 / 1

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

USA