

Safety Data Sheet
acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

1 Identification

- **Product identifier**
- **Trade name:** *Parabond M-250 Contact Adhesive, Solvent Based*
- **Relevant identified uses of the substance or mixture.** *No further relevant information available.*
- **Details of the supplier of the safety data sheet**
- **Company information:**
*H.B. Fuller Construction Products Inc.
1105 S. Frontenac Street
Aurora, IL 60504
Information Phone Number: 1-800-552-6225*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:** *ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

*Repr. 2 H361 Suspected of damaging fertility or the unborn child.**STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.**Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.*

GHS07

*Skin Irrit. 2 H315 Causes skin irritation.**Eye Irrit. 2A H319 Causes serious eye irritation.**STOT SE 3 H336 May cause drowsiness or dizziness.*

- **Label elements**

- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

- **Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 1)

Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.


· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 3
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = *2
 FIRE 3 Fire = 3
 PHYSICAL HAZARD 0 Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

* 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

110-54-3	n-hexane	25-50%
67-64-1	acetone	25-50%
108-88-3	toluene	5-20%

* 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Wipe excess from skin.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 2)

- Immediately wash with water and soap and rinse thoroughly.*
- **After eye contact:** *Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.*
- **After swallowing:**
Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *CO2, extinguishing powder or water spray. Fight larger fires with water spray.*
- **For safety reasons unsuitable extinguishing agents:** *Water*
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:** *Protective clothing and respiratory protective device.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Avoid prolonged or repeated contact with skin.
Avoid contact with eyes.
Wash thoroughly after handling.
Open containers in a well ventilated area and avoid breathing headspace vapors.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep container closed when not in use.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
 - Protect from contamination.
 - Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-54-3 n-hexane (25-50%)

PEL	Long-term value: 1800 mg/m ³ , 500 ppm
REL	Long-term value: 180 mg/m ³ , 50 ppm
TLV	Long-term value: 176 mg/m ³ , 50 ppm
	Skin; BEI

67-64-1 acetone (25-50%)

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm
	Long-term value: (1188) NIC-475 mg/m ³ , (500) NIC-200 ppm
	BEI

108-88-3 toluene (5-20%)

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm
	BEI

· **Ingredients with biological limit values:**

110-54-3 n-hexane (25-50%)

BEI	0.4 mg/L
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: 2.5-Hexanedione without hydrolysis

67-64-1 acetone (25-50%)

BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 4)

108-88-3 toluene (5-20%)

BEI 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:** Protective work clothing

USA

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 5)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Tan
· Odor:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point:	Undetermined.
· Boiling point:	55 °C (131 °F)

· **Flash point:** -26 °C (-15 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Flammable limits:**

· Lower:	1.2 Vol %
· Upper:	13.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 233 hPa (175 mm Hg)

· **Specific gravity at 20 °C (68 °F):** 0.675 g/cm³ (5.633 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic:	Not determined.

· **Solvent content:**

· **VOC (Per EPA 24)**

· **Other information**

not available GMS/L
 California VOC Compliance:
 Contains Solvent
 SCAQMD Rule 1168: Not VOC Compliant
 Grams VOC [less water, less exempts] 351 grams/liter of material
 Grams VOC [less water, less exempts] 523 grams/liter of coating
 SCAQMD Rule 443.1: 574 grams/liter of material
 574 grams/liter of coating

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** not reactive, as supplied.
- **Conditions to avoid** Heat, flames, sparks.
- **Incompatible materials:** Reacts with oxidizing agents.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrocarbons

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Skin irritant.
- **on the eye:**
May be severely irritating to the eyes.
Vapors may be irritating to the eyes.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
----------	---------	---

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxic effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based






(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="margin-left: 20px;">UN1133</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG · IATA | <p style="margin-left: 20px;">Adhesives
1133 Adhesives, ENVIRONMENTALLY HAZARDOUS
ADHESIVES (HEXANES), MARINE POLLUTANT
ADHESIVES</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="display: flex; align-items: center; gap: 10px;">   </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids.
3</p> |
| | |
| <ul style="list-style-type: none"> · ADR, IMDG | <div style="display: flex; align-items: center; gap: 10px;">   </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids
3</p> |
| | |
| <ul style="list-style-type: none"> · IATA | <div style="display: flex; align-items: center; gap: 10px;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids.
3</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA | <p style="margin-left: 20px;">II</p> |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 8)

· Environmental hazards:	Product contains environmentally hazardous substances: <i>n</i> -hexane
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Remarks:	Special marking with the symbol (fish and tree).
· UN "Model Regulation":	UN1133, Adhesives, ENVIRONMENTALLY HAZARDOUS, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3 *n*-hexane

108-88-3 toluene

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity:**

108-88-3 toluene

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

110-54-3 *n*-hexane

II

67-64-1 acetone

I

108-88-3 toluene

II

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

108-88-3 toluene

A4

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 02/17/2014

Revision Number 1

Revision Date 02/17/2014

Trade name: Parabond M-250 Contact Adhesive, Solvent Based

(Contd. of page 9)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **National regulations:**

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* 16 Other information

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, H.B. Fuller Construction Products Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will H.B. Fuller Construction Products Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

· **Department issuing MSDS:** Environment protection department.

· **Creation Date:** 02/13/2014

· **Date of preparation / last revision** 02/17/2014 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1