

Safety Data Sheet
acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

1 Identification

- **Product identifier**
- **Trade name:** *Parabond M-363 Seam Sealer*
- **Relevant identified uses of the substance or mixture.** *Adhesive*
- **Details of the supplier of the safety data sheet**
- **Company information:**
*H.B. Fuller Construction Products Inc.
1105 S. Frontenac Street
Aurora, IL 60504
1-800-552-6225*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:** *ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887*

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS07



GHS08

- **Signal word** *Warning*
- **Hazard statements**
*Causes skin irritation.
Causes eye irritation.
Suspected of causing cancer.*
- **Precautionary statements**
*If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.*

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 1)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 1

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	1
PHYSICAL HAZARD	0

Health = *2

Fire = 1

Physical Hazard = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

* 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Adhesive

· **Dangerous components:**

75-09-2	dichloromethane (Methylene Chloride)		
---------	--------------------------------------	--	--

			50-100%
--	--	--	---------

* 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Call a doctor immediately.

Overexposure, remove to fresh air and seek medical attention.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.

· **After swallowing:**

Rinse out mouth with water. Drink 1 - 2 glasses of water but **DO NOT** induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

USA

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Mount respiratory protective device.
Remove persons from danger area.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Prevent formation of aerosols.
Open containers in a well ventilated area and avoid breathing headspace vapors.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store above 40F and below 100F.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: **Parabond M-363 Seam Sealer**

(Contd. of page 3)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

75-09-2 dichloromethane (Methylene Chloride) (50-100%)

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m ³ , 50 ppm BEI

- **Ingredients with biological limit values:**

75-09-2 dichloromethane (Methylene Chloride) (50-100%)

BEI	0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment (see listings below)**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

- **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

USA

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 4)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Clear
· Odor:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point:	Undetermined.
· Boiling point:	40 °C (104 °F)

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 605 °C (1121 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Flammable limits:**

· Lower:	13.0 Vol %
· Upper:	22.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 453 hPa (340 mm Hg)

· **Specific gravity at 20 °C (68 °F):** 1.16 g/cm³ (9.68 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **Dynamic:** Not determined.

· **Kinematic:** Not determined.

· **Other information**

California VOC Compliance:
NOT compliant in the state of California. Contains Methylene Chloride.

10 Stability and reactivity

· **Reactivity**

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid**

Exposure to high temperatures.

Temperatures below 40F (4.4C)

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 5)

- **Incompatible materials:**
 - Reacts with oxidizing agents.
 - Reacts with strong alkali.
- **Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide
 - Hydrogen chloride (HCl)
 - Chlorine
 - Phosgene
 - Hydrocarbons

* 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

75-09-2 dichloromethane (Methylene Chloride)

Oral	LD50	1600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Skin irritant.
- **on the eye:**
 - May irritate the eye.
 - Vapors may be severely irritating to the eyes.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Toxic
 - Irritant
 - Carcinogenic.
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

75-09-2	dichloromethane (Methylene Chloride)	2B
---------	--------------------------------------	----

· **NTP (National Toxicology Program)**

75-09-2	dichloromethane (Methylene Chloride)	R
---------	--------------------------------------	---

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT · ADR, IMDG, IATA | <p style="margin-left: 20px;">UN2206</p> <p style="margin-left: 20px;">UN1593</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | <p style="margin-left: 20px;">Isocyanates, toxic, n.o.s. (Dichloromethane)</p> <p style="margin-left: 20px;">1593 Dichloromethane, solution</p> <p style="margin-left: 20px;">DICHLOROMETHANE, solution</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center; margin-bottom: 10px;"> </div> <p style="margin-left: 20px;">6.1 Toxic substances.</p> <p style="margin-left: 20px;">6.1</p> |
| <ul style="list-style-type: none"> · ADR, IMDG, IATA | <div style="text-align: center; margin-bottom: 10px;"> </div> <p style="margin-left: 20px;">6.1 Toxic substances</p> <p style="margin-left: 20px;">6.1</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA | <p style="margin-left: 20px;">III</p> |
| <ul style="list-style-type: none"> · Environmental hazards: | <p style="margin-left: 20px;">Not applicable.</p> |
| <ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups | <p style="margin-left: 20px;">Warning: Toxic substances</p> <p style="margin-left: 20px;">60</p> <p style="margin-left: 20px;">F-A,S-A</p> <p style="margin-left: 20px;">Liquid halogenated hydrocarbons</p> |
| <ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <p style="margin-left: 20px;">Not applicable.</p> |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 7)

· UN "Model Regulation": UN1593, Dichloromethane, solution, 6.1, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Proposition 65

· Chemicals known to cause cancer:

All ingredients are listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Domestic Substance List

All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

75-09-2 dichloromethane (Methylene Chloride)

B2

· TLV (Threshold Limit Value established by ACGIH)

75-09-2 dichloromethane (Methylene Chloride)

A3

· MAK (German Maximum Workplace Concentration)

75-09-2 dichloromethane (Methylene Chloride)

3A

· NIOSH-Ca (National Institute for Occupational Safety and Health)

All ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

All ingredients are listed.

· National regulations:

- Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* 16 Other information

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, H.B. Fuller Construction Products Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will H.B. Fuller Construction Products Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

- Department issuing MSDS: Environment protection department.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing Date 01/06/2014

Revision Number 1

Revision Date 01/06/2014

Trade name: Parabond M-363 Seam Sealer

(Contd. of page 8)

· **Creation Date:** 01/06/2014· **Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent*

USA