

**Safety Data Sheet**  
acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**1 Identification**

- **Product identifier**
- **Trade name:** *Parabond V-260 VOC Compliant Pad Cement*
- **Relevant identified uses of the substance or mixture.** *Adhesive*
- **Details of the supplier of the safety data sheet**
- **Company information:**  
*H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
1-800-552-6225*
- **Information department:** *Environment protection department.*
- **Emergency telephone number:**  
*ChemTrec: Day or Night within USA and Canada: 1-800-424-9300.  
Outside USA and Canada: +1 703-527-3887 (collect calls accepted)*

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

*Flam. Liq. 2 H225 Highly flammable liquid and vapor.*



GHS07

*Eye Irrit. 2A H319 Causes serious eye irritation.*

*STOT SE 3 H336 May cause drowsiness or dizziness.*

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** *Danger*
- **Hazard statements**  
*Highly flammable liquid and vapor.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.*
- **Precautionary statements**  
*If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 1)

Use explosion-proof electrical/ventilating/lighting/equipment.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wear protective gloves / eye protection / face protection.  
 Wear eye protection / face protection.  
 Ground/bond container and receiving equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store locked up.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1  
 Fire = 3  
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 1  
 Fire = 3  
 Physical Hazard = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### \* 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture**

- **Hazardous components:**

67-64-1	acetone	50-100%
---------	---------	---------

### \* 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**  
 Supply fresh air or oxygen; call for doctor.  
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
 Wipe excess from skin.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 2)

- Immediately wash with water and soap and rinse thoroughly.*
- **After eye contact:** *Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.*
- **After swallowing:**  
*Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.*  
*Seek medical treatment.*
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
*CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.*
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:** *Protective clothing and respiratory protective device.*

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
*Wear protective equipment. Keep unprotected persons away.*  
*Ensure adequate ventilation*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*  
*Dispose of contaminated material as waste in accordance with federal state and local regulations.*  
*Ensure adequate ventilation.*
- **Reference to other sections**  
*See Section 7 for information on safe handling.*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for disposal information.*

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
*Avoid prolonged or repeated contact with skin.*  
*Avoid contact with eyes.*  
*Wash thoroughly after handling.*  
*Prevent formation of aerosols.*  
*Open containers in a well ventilated area and avoid breathing headspace vapors.*
- **Information about protection against explosions and fires:**  
*Keep container closed when not in use.*  
*Keep ignition sources away - Do not smoke.*  
*Protect against electrostatic charges.*

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

#### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm BEI

- **Ingredients with biological limit values:**

#### 67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment (see listings below)**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 4)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:** Protective work clothing

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	Not determined.
· <b>Odor:</b>	Characteristic
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point:</b>	Undetermined.
· <b>Boiling point:</b>	55 °C (131 °F)

· **Flash point:** -19 °C (-2 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 465 °C (869 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Flammable limits:**

· <b>Lower:</b>	2.6 Vol %
· <b>Upper:</b>	13.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 233 hPa (175 mm Hg)

· **Specific gravity at 20 °C (68 °F):** 0.86 g/cm<sup>3</sup> (7.177 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not soluble

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **Dynamic:** Not determined.

(Contd. on page 6)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 5)

<b>Kinematic:</b>	Not determined.
<b>Solvent content:</b> VOC (Per EPA 24)	not available GMS/L
<b>Solids content:</b> <b>Other information</b>	not available Pounds Per Gallon 7.19 Grams VOC/Liter [less water, less exempts] 0.0

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flames, sparks.
- **Incompatible materials:**  
Strong oxidizers, acids, and bases.  
Reacts with oxidizing agents.  
Halogens
- **Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Hydrocarbons

## 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**
- |   |      |                      |
|---|------|----------------------|
| · <b>LD/LC50 values that are relevant for classification:</b> |      |                      |
| <b>67-64-1 acetone</b>  |      |                      |
| Oral  | LD50 | 5800 mg/kg (rat)     |
| Dermal  | LD50 | 20000 mg/kg (rabbit) |
- **Primary irritant effect:**
  - **on the skin:** May irritate the skin.
  - **on the eye:**  
Irritating effect.  
Vapors may be irritating to the eyes.
  - **Sensitization:** No sensitizing effects known.
  - **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
  - **Carcinogenic categories**
- |   |
|---|
| · <b>IARC (International Agency for Research on Cancer)</b> |
| None of the ingredients is listed.                          |
- |  |
|--|
| · <b>NTP (National Toxicology Program)</b> |
| None of the ingredients is listed.         |

(Contd. on page 7)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.


### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport information

- |                                     |   |
|-------------------------------------|---|
| · <b>UN-Number</b>                  |   |
| · <b>DOT, ADR, IMDG, IATA</b>       | UN1133  |
| · <b>UN proper shipping name</b>    |   |
| · <b>DOT</b>                        | Adhesives   |
| · <b>ADR</b>                        | 1133 Adhesives, solution  |
| · <b>IMDG, IATA</b>                 | ADHESIVES, solution   |
| · <b>Transport hazard class(es)</b> |   |
| · <b>DOT</b>                        |   |
|                                     |  |
| · <b>Class</b>                      | 3 Flammable liquids   |
| · <b>Label</b>                      | 3   |

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

Trade name: **Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 7)

· **ADR, IMDG, IATA**

· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3
· <b>Packing group</b>	II
· <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E,S-D
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	UN1133, Adhesives, solution, 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 · Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity:**

None of the ingredients is listed.

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1 | acetone

I

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 | acetone

A4

· **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

(Contd. on page 9)



# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 05/05/2015

Revision Number 1

Revision Date 05/05/2015

**Trade name: Parabond V-260 VOC Compliant Pad Cement**

(Contd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, H.B. Fuller Construction Products Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will H.B. Fuller Construction Products Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:** Environment protection department.

· **Creation Date:** 01/02/2014

· **Date of preparation / last revision** 05/05/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

USA