



Parabond M-267

Premium Latex Carpet Edge Sealer

PARABOND ACCESSORIES

DESCRIPTION:

Parabond M-267 Premium Latex Carpet Seaming Adhesive is a natural latex adhesive designed for the application of carpet seaming and reinforcing tapes. It may also be used for replacing damaged or burned nap, sealing raw edges, strengthening worn backing and joining padding.

Parabond M-267 Premium Latex Carpet Seaming Adhesive is extremely fast drying, easy spreading, non-toxic, non-flammable and colorless when dry. Bonding strength increases with age and will not deteriorate after shampooing.

SURFACE PREPARATION:

Be sure all surfaces are clean, dry and free of dust, wax or any type of polish.

DIRECTIONS:

Shake container well before using.

BACK SEAMING:

1. Spread adhesive the length of the seam making sure you have even coverage.
2. Scrape excess adhesive toward center of the seam. Heavier ribbed carpet requires more adhesive.
3. Unroll seaming tape the length of the seam and tack both ends.
4. Smooth the entire length of the tape's surface to adhere tape and remove any wrinkles.
5. Allow to dry.

FACE SEAMING:

1. Unroll face seaming tape the length of the seam and apply adhesive.
2. Tape should be centered and tacked at both ends.
3. Smooth seam against tape.
4. Avoid too much pressure as you do not want to force adhesive into carpet face.
5. Allow to dry.

6. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

CAUTION: This product may cause staining to hardwood, linoleum, etc. Immediate clean-up is recommended.

COVERAGE:

One Quart provides Approx. 340 linear feet of 1/8" bead.

CLEAN UP:

Adhesive may be removed from carpet while still wet by repeated sponging with water and detergent. If adhesive has dried on the carpet, use PARABOND M-315 CLEANER/SOLVENT. Do not allow solvent to soak into the carpet; it will destroy the adhesive bond.

PHYSICAL PROPERTIES:

Weight/gallon (lbs)	8.0
Consistency	Off-white Liquid
Set up time	30 to 60 seconds with pressure
Freeze thaw stable @	Temperatures of 20°F or higher
Shelf Life	1 year in unopened container

FOR MORE INFORMATION READ MATERIAL SAFETY DATA SHEET

KEEP OUT OF REACH OF CHILDREN

WARRANTY:

H.B. Fuller Construction Products offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800-832-9023 or visiting www.parabond.com.