

## **Product Sustainability Quick Reference Guide**

## **Our Focus on the Environment**

Parabond® products are developed and manufactured with the environment in mind. Our goal is simple: Develop products that balance sustainability, usability, performance and value.

Product name	VOC CONTENT g/L less water	MAS CERTIFIED GREEN: CDPH VOC Emissions	FLOORSCORE	CRI	EPD Industry-wide Type III	HPD (any are available upon request)
Signature Series DS-902 Dubl-Stik Adhesive	<1	•	•	•		
Signature Series 4092 Economy Grade Flooring Adhesive	n/a	•	•	•		
Signature Series 4094 Premium Multi Purpose Adhesive	<1	•	•	•		
Signatre Series 4096 Fast Grab Multi Purpose Adhesive	0.77	•	•	•		
Signature Series 4099 High Performance Multi Purpose Adhesive	<1	•	•	•		
Fusion Series 5082 Vinyl Tile & Plank Adhesive	<1	•	•	•		
Signature Series 5060 Pressure Sensitive Adhesive	<1	•	•	•		
Signature Series 5080 Pressure Sensitive Adhesive	6	•	•	•		
Fusion Series 4500 Clear Thin Spread VCT	<1	•	•	•		
Fusion Series 4700 Rubber Tile and Stair Tread Adhesive	<10	•	•	•		
Parabond M-4263 Solvent-Free Universal Carpet Seam Sealer	<21	•	•	•		
Fusion X Wall Base Adhesive	<1	•	•	•		
Fusion Series 5092 HT Universal Pressure Sensitive Adhesive	<1	•	•	•		
AIM™ 382 Solvent-Free Pedestal Adhesive	0	•	•	•		
Millennium Series 2009 Premium Wood Flooring Adhesive	<8	•	•	•		
M-2850 Outdoor & Indoor Carpet Adhesive	<1	•	•	•		

Reference Guide for Applicable Credits						
Low-Emitting Materials Points		Requirement				
IEQ Credit 4.2	1	All paints and coatings (including floor coatings, primers and sealers) must not exceed the VOC content limits established in South Coast Air Quality Management District (SCAQMD) Rule #1113. SCAQMD #1168 sets volatile organic compound limits for paints and coatings applied on site.				

