

**SCS Global Services** does hereby certify that an independent assessment has been conducted on behalf of:

# H.B. Fuller Construction Products/ Royal Adhesives and Sealants

1702 Kimberly Park Dr., Dalton, GA, United States

For the following product(s):

See Addendum

The product(s) meet(s) all of the necessary qualifications to be certified for the following claim(s):

## FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Standard Product Application Amount: 5027 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): 0.5 – 5.0 mg/m<sup>3</sup> (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-FS-07317

Valid from: November 1, 2023 to September 30, 2024



A handwritten signature in black ink that reads 'Stanley Mathuram'.

Stanley Mathuram, PE, Executive Vice President  
SCS Global Services  
2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

## **Certification Addendum**

# **H.B. Fuller Construction Products/ Royal Adhesives and Sealants**

Certification: Registration # SCS-FS-07317 | Valid from: November 1, 2023 to September 30, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, <http://www.scsglobalservices.com/certified-green-products-guide>.

Addendum **FloorScore®**

Conformance: Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Standard Product Application Amount: 5027 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): 0.5 – 5.0 mg/m<sup>3</sup> (in compliance with CDPH/EHLB Standard

Products: **Multi-Purpose Adhesives:**

Chapco Safe Set 3, Chapco Safe Set 7, TEC 700, TEC 717, PARABOND M-2850, TEC 902, TEC 975, TEC Skill Set Outdoor Carpet Adhesive, Signature Series DS-902, Signature Series 4092, Signature Series 4094, Signature Series 4096, Signature Series 4099, M-2850