



M-363

All Purpose Seam Sealer Non Flammable

ACCESSORIES

DESCRIPTION:

Parabond M-363 All-Purpose Seam Sealer is recommended for seaming all carpets with jute or synthetic secondary backing, sponge rubber, high density foam backing (including Dow's Enhancer) and latex unitary.

The M-363 is a must for double stick glue down, direct glue down and stretch-in applications. The M-363 is excellent for bonding tack strip to structurally sound concrete surfaces.

M-363 is **Not Recommended** for use with PVC/Vinyl backed carpeting.

DIRECTIONS:

1. Prepare carpet according to manufacturer's instructions. Refer to CRI Carpet Installation Standard 2009 for additional information regarding subfloor preparations, etc.
2. Apply a bead of seam adhesive along one side of the trimmed edge where the face yarn enters the backing using an application bottle.
3. Complete the seam by butting both sections of the carpet together while the adhesive is still wet (within 5 minutes).
4. If the seam tends to separate, relieve the stress on the carpet with a knee kicker.
5. Avoid soaking carpet with solvent. Do Not pour solvent directly on carpet.
6. For tack strip application, apply a generous bead of adhesive to the back of each piece of strip.
7. Put the tack strip in place, remove briefly, allowing the solvent to flash, then re-install.
8. This will permit the contact bond to gain strength quickly.
9. Allow the adhesive to cure completely before installing the carpet.
10. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

COVERAGE:

One quart provides approx. 350 linear ft of 1/8" bead.

CLEAN-UP:

Use Parabond M-315 Reducer/Cleaner to remove wet adhesive from carpet yarn. Adhesive smears on the carpet surface are easily cleaned within ten minutes by gentle daubing/rubbing with a clean white cloth, wet with Parabond M-315.

FOR PROFESSIONAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

FOR MORE INFORMATION READ MATERIAL SAFETY DATA SHEET

SHELF LIFE:

Maximum of 12 months from date of manufacture in unopened container.

LIMITED WARRANTY:

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **TEC Specialty Products LLC disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit parabond.com. To obtain a hard copy of the Limited Warranty call TEC Specialty Products at 800-832-9023 or mail a written request to the address in the bottom of this Product Data Sheet.



TEC Specialty Products LLC
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
parabond.com