



# M-4263

## Solvent Free Universal Carpet/Vinyl Seam Adhesive

# ACCESSORIES

### DESCRIPTION:

Parabond M-4263 is a solvent free universal carpet/vinyl seam adhesive for use with all types of carpet backings in direct glue down installations, including vinyl backed carpet, cushion-backed vinyl flooring and fiberglass backed vinyl flooring.

### DIRECTIONS:

1. Prepare flooring according to manufacturer's instructions.
2. Refer to CRI Carpet Installation Standard 2009 (or ASTM F710) for additional information regarding subfloor preparations, etc.
3. Apply a bead of seam adhesive along the trimmed edge (one side) of the flooring or where the face yarn enters the backing for carpet.
4. Complete the seam by butting both sections of the flooring together while the adhesive is still wet (within 5-10 minutes).
5. If the seam tends to buckle, relieve the stress on the flooring.
6. Adhesive smears are easily cleaned with a damp cloth wet with water within 15 minutes. Use Mineral Spirits to remove dried adhesive. Avoid soaking carpet with solvent. Do not pour solvent directly on flooring.

### RECOMMENDED APPLICATIONS:

- Broadloom Carpet
- Cushion-Backed Sheet Vinyl
- Fiberglass-Backed Sheet Flooring

### RESTRICTIONS:

1. For Interior installations only.
2. Do not install over adhesive residue including cutback.
3. Do not install when ambient temperature is not between 60°F & 95°F.
4. Do not install when ambient relative humidity is above 65%.
5. It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the user's intended use.

### FOR PROFESSIONAL USE ONLY

### COVERAGE:

One quart (32 oz.) provides approx. 340 linear feet of 1/8" bead

One 8 oz. bottle provides approx. 85 linear feet of 1/8" bead

### CLEAN-UP:

Fresh adhesive can be removed immediately with a damp cloth. If adhesive has dried, use waterless hand cleaner, Mineral Spirits, or M-315 Cleaner. Do not allow solvent to penetrate seams. Solvent will dissolve adhesive bond.

**CAUTION: Mineral Spirits are flammable. Read and follow all precautions on container label.**

### PACKAGING:

- One – 8 oz Applicator Bottle
- One – 32 oz Applicator Bottle

### KEEP OUT OF REACH OF CHILDREN

### SHELF LIFE:

Maximum of 12 months from date of manufacture in unopened container.

### LIMITED WARRANTY:

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **TEC Specialty Products LLC disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit [parabond.com](http://parabond.com). To obtain a hard copy of the Limited Warranty call TEC Specialty Products at 800-832-9023 or mail a written request to the address in the bottom of this Product Data Sheet.



TEC Specialty Products LLC  
1105 South Frontenac Street  
Aurora, IL 60504-6451 U.S.A.  
[parabond.com](http://parabond.com)