

PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PARABOND® MILLENNIUM SERIES 4010

Product code : 100000012014

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 800-832-9023

Medical Emergency Phone Number (24 Hours): 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Isocyanate based product, Polyurethane resin

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	paste	
Color	light yellow	
Odor	characteristic	

GHS Classification

Skin irritation : Category 2
Eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Specific target organ toxicity - : Category 2

repeated exposure

GHS label elements

Hazard pictograms

Signal Word : Danger



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

Hazard Statements:

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection. P285 In case of inadequate ventilation wear respiratory protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor. P362 Take off contaminated clothing and wash before reuse.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Aggravated Medical

Condition

: None known.

Symptoms of Overexposure : Breathing difficulties

Carcinogenicity:

IARC Group 1: Carcinogenic to humansDuring normal handling of the

product, this substance is encapsulated within the product and

will not present a cancer exposure risk. Quartz (SiO2) 14808-60-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogenDuring normal handling of the product, this substance is encapsulated within the product and

will not proceed a concern over course risk

will not present a cancer exposure risk. Quartz (SiO2) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Calcium carbonate	471-34-1	50 - 70
Isocyanate Based Polymer	9048-57-1	10 - 20
glass, oxide, chemicals, non-fibrous	65997-17-3	1 - 5
Sodium borosilicate	50815-87-7	1 - 5



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

4,4'-Methylenediphenyl diisocyanate	101-68-8	1 - 5
Quartz (SiO2)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Get medical attention if irritation develops and persists.

Take off contaminated clothing and shoes immediately.

Wash contaminated clothing before re-use.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

If swallowed : Do not induce vomiting. If conscious, give 2 glasses of water.

Get immediate medical attention.

Most important symptoms and effects, both acute and

delayed

: Breathing difficulties

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

: Burning produces irritant fumes.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleaning up : Refer to protective measures listed in sections 7 and 8.

: Soak up with inert absorbent material. Shovel into suitable container for disposal. Neutralize with the following product(s):

Ammonia

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Protect from moisture.

Avoid inhalation, ingestion and contact with skin and eyes.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	PEL (Total dust)	10 mg/m3	CAL PEL
		PEL (respirable dust fraction)	5 mg/m3	CAL PEL
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
glass, oxide, chemicals, non- fibrous	65997-17-3	TWA	1 fibres per cubic centimeter	ACGIH
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA	1 fibres per cubic centimeter	ACGIH
		TWA (fibers)	1 fibres per cubic centimeter	ACGIH
		TWA (fibers)	1 fibres per cubic centimeter	ACGIH
4,4'-Methylenediphenyl	101-68-8	TWA	0.005 ppm	ACGIH



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

diisocyanate				
		С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.2 ppm 0.2 mg/m3	NIOSH REL
		TWA	0.005 ppm	ACGIH
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	NIOSH REL
		PEL	0.005 ppm 0.051 mg/m3	CAL PEL
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management

measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within

recommended exposure guidelines.



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.

Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste
Color : light yellow
Odor : characteristic
Odor Threshold : no data available
pH : Not applicable
Melting point/freezing point : is not determined

Initial boiling point and boiling

range

: is not determined

Flash point : 100 °CMethod: closed cupNot applicable

Evaporation rate : is not determined

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined

Density : 1.27 g/cm3

Solubility(ies)

Water solubility : is not determined Partition coefficient: n- : no data available

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Container can be pressurized by carbon dioxide due to

reaction with humid air and/or water.

Chemical stability : The product is chemically stable.



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

Possibility of hazardous

reactions

Incompatible materials

: Hazardous polymerization does not occur.

: Amines

Strong acids and strong bases

Hazardous decomposition

products

: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : 72.86 mg/l

Exposure time: 4 Hours
Test atmosphere: dust/mist
Method: Calculation method

Components:

4,4'-Methylenediphenyl diisocyanate:

Acute inhalation toxicity : Acute toxicity estimate : 1.5 mg/l

Test atmosphere: dust/mist Method: Expert judgment

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure



PARABOND® MILLENNIUM SERIES 4010

Version 1.0

Revision Date 09/10/2025

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



PARABOND® MILLENNIUM SERIES 4010

Version 1.0 Revision Date 09/10/2025

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

4,4'-Methylenediphenyl diisocyanate 101-68-8 9016-87-9 Polymethylene polyphenyl

isocyanate

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

> 4,4'-Methylenediphenyl diisocyanate 101-68-8

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory DSL All components of this product are on the Canadian DSL

Please reach out to TEC Specialty Products LLC for further information regarding chemical inventories not listed above. Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION




PARABOND® MILLENNIUM SERIES 4010

Version 1.0

Revision Date 09/10/2025

Further information





Special hazard

HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic