

SAFETY DATA SHEET

PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PARABOND® M-250
Product code : 100000012016

Manufacturer or supplier's details

Company : TEC Specialty Products
Address : 1105 South Frontenac
Aurora, IL, 60504
Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours) : 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	tan
Odor	characteristic

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure : Category 2
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

SAFETY DATA SHEET**PARABOND® M-250**

Version 1.0

Revision Date 03/14/2025

Hazard Statements:

H225 Highly flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects**Carcinogenicity:****IARC**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
n-hexane	110-54-3	30 - 50

SAFETY DATA SHEET

PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

acetone	67-64-1	30 - 50
Toluene	108-88-3	20 - 30

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Take the victim into fresh air.
- If inhaled : If inhaled
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Oxygen or artificial respiration if needed.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Get medical attention if irritation develops and persists.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this SDS.
If conscious, drink plenty of water.
Never give anything by mouth to an unconscious person.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
No hazardous combustion products are known
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods :
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SAFETY DATA SHEET

PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.
Should not be released into the environment.
- Methods and materials for containment and cleaning up : Ventilate the area.
Soak up with inert absorbent material.
Shovel into suitable container for disposal.
Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Use only with adequate ventilation/personal protection.
Keep away from fire, sparks and heated surfaces.
Avoid formation of aerosol.
Keep container closed when not in use.
Ensure all equipment is electrically grounded before beginning transfer operations.
- Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.
Use explosion-proof equipment.
Keep container tightly closed in a dry and well-ventilated place.
Store in original container.
Solvent vapors are heavier than air and may spread along floors.
- Materials to avoid : Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
n-hexane	110-54-3	TWA	50 ppm	ACGIH
		TWA	50 ppm	NIOSH REL

SAFETY DATA SHEET

PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

			180 mg/m3	
		TWA	500 ppm 1,800 mg/m3	OSHA Z-1
		TWA	50 ppm 180 mg/m3	OSHA P0
		PEL	50 ppm 180 mg/m3	CAL PEL
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		C	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		STEL	150 ppm 560 mg/m3	OSHA P0
		TWA	100 ppm 375 mg/m3	OSHA P0
		PEL	10 ppm 37 mg/m3	CAL PEL
		C	500 ppm	CAL PEL
		STEL	150 ppm 560 mg/m3	CAL PEL

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

SAFETY DATA SHEET

PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

Hand protection	
Material	: butyl-rubber
Eye protection	: Safety glasses with side-shields
Skin and body protection	: Long sleeved clothing Remove and wash contaminated clothing before re-use. Skin should be washed after contact.
Protective measures	: Avoid contact with skin.
Hygiene measures	: Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: tan
Odor	: characteristic
Odor Threshold	: no data available
pH	: is not determined
	: is not determined
	: 56 °C
	is not determined
Flash point	: -29 °C
Evaporation rate	: is not determined
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower explosion limit is not determined
Vapor pressure	: is not determined
Density	: 0.816 g/cm3 (20 °C)
Solubility(ies)	
Water solubility	: immiscible is not determined
Partition coefficient: n-octanol/water	: no data available
Autoignition temperature	: 240 °C is not determined
Viscosity	
Viscosity, kinematic	: is not determined

SAFETY DATA SHEET**PARABOND® M-250**

Version 1.0

Revision Date 03/14/2025

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**n-hexane:**

Acute dermal toxicity : LD50 Dermal Rabbit: 3,000 mg/kg

Toluene:

Acute oral toxicity : LD50 Oral Rat: 5,580 mg/kg

Acute inhalation toxicity : LC50 Rat: 12.5 mg/l
Exposure time: 4 h

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

SAFETY DATA SHEET**PARABOND® M-250**

Version 1.0

Revision Date 03/14/2025

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****n-hexane :**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.1 - 2.98 mg/l
Exposure time: 96 h
Test Method: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential**Components:****acetone :**

Partition coefficient: n-octanol/water : log Pow: -0.24

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of together with household waste. The hazard and precautionary statements displayed on the label also apply to any residues left in the container. Do not dispose of waste into sewer. To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more

SAFETY DATA SHEET

PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1133
Proper shipping name : ADHESIVES (HEXANE)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET**PARABOND® M-250**

Version 1.0

Revision Date 03/14/2025

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

n-hexane	110-54-3
Toluene	108-88-3

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

n-hexane	110-54-3
Toluene	108-88-3

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory

DSL All components of this product are on the Canadian DSL

Please reach out to TEC Speciality Products, LLC for further information regarding chemical inventories not listed above. **Inventories Legend** TSCA (USA), DSL (Canada), REACH (Europe), AIIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET


PARABOND® M-250

Version 1.0

Revision Date 03/14/2025

Further information

NFPA:



HMIS III:

HEALTH	3*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the TEC Specialty Products, LLC from its suppliers, and because the TEC Specialty Products, LLC has no control over the conditions of handling and use, the TEC Specialty Products, LLC makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the TEC Specialty Products, LLC assumes no responsibility for use or reliance thereon. It is the responsibility of the user of TEC Specialty Products, LLC to comply with all applicable federal, state and local laws and regulations.