

PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PARABOND® M-163
Product code : 100000012017

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid	
Color	yellow	
Odor	characteristic	

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 2

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Specific target organ toxicity - : Category 2

repeated exposure

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms







Signal Word : Danger



PARABOND® M-163

Version 1.0

Revision Date 03/14/2025

Hazard Statements:

H225 Highly flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens. No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Additional Labeling:

NTP

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

13.734 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	20 - 30
n-hexane	110-54-3	10 - 20
Mineral oil	64742-52-5	10 - 20
Toluene	108-88-3	5 - 10

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

: In the case of accident or if you feel unwell, seek medical General advice

advice immediately.

Take the victim into fresh air.

If inhaled : If inhaled

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Oxygen or artificial respiration if needed.

In case of skin contact : Wash off immediately with soap and plenty of water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do not induce vomiting. Seek medical attention if symptoms

develop. Provide medical care provider with this SDS.

If conscious, drink plenty of water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

: May be fatal if swallowed and enters airways.

Causes skin irritation. Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility. Suspected of damaging the

unborn child.

May cause damage to organs through prolonged or repeated

exposure.



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

No hazardous combustion products are known

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing methods

Further information

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment

for fire-fighters

: Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.

Should not be released into the environment.

Methods and materials for containment and cleaning up

Ventilate the area.

Soak up with inert absorbent material. Shovel into suitable container for disposal.

Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Use only with adequate ventilation/personal protection.

Keep away from fire, sparks and heated surfaces.

Avoid formation of aerosol.

Keep container closed when not in use.

Ensure all equipment is electrically grounded before beginning

transfer operations.



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Keep container tightly closed in a dry and well-ventilated

place.

Store in original container.

Solvent vapors are heavier than air and may spread along

floors.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
n-hexane	110-54-3	TWA	50 ppm	ACGIH
		TWA	50 ppm 180 mg/m3	NIOSH REL
		TWA	500 ppm 1,800 mg/m3	OSHA Z-1
		TWA	50 ppm 180 mg/m3	OSHA P0
		PEL	50 ppm 180 mg/m3	CAL PEL
Mineral oil	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

I	1	ST (Mist)	10 mg/m3	NIOSH REL
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL
		(particulate)		
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
			375 mg/m3	
		ST	150 ppm	NIOSH REL
			560 mg/m3	
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		STEL	150 ppm	OSHA P0
			560 mg/m3	
		TWA	100 ppm	OSHA P0
			375 mg/m3	
		PEL	10 ppm	CAL PEL
			37 mg/m3	
		С	500 ppm	CAL PEL
		STEL	150 ppm	CAL PEL
			560 mg/m3	

Engineering measures : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management

measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within

recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Material : butyl-rubber

Eye protection : Safety glasses with side-shields

Skin and body protection : Long sleeved clothing

Remove and wash contaminated clothing before re-use.

Skin should be washed after contact.

Protective measures : Avoid contact with skin.



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Color : yellow
Odor : characteristic
Odor Threshold : no data available
pH : is not determined

: is not determined: is not determined

Flash point : < -7 °C

Evaporation rate : is not determined Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower explosion limit

is not determined

Vapor pressure : is not determined

Density : 7.0 - 7.4 lb/gal

Solubility(ies)

Water solubility : is not determined
Partition coefficient: n- : no data available

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

Method: Calculation method

Components:

n-hexane:

Acute dermal toxicity : LD50 Dermal Rabbit: 3,000 mg/kg

Toluene:

Acute oral toxicity : LD50 Oral Rat: 5,580 mg/kg

Acute inhalation toxicity : LC50 Rat: 12.5 mg/l

Exposure time: 4 h

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

n-hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.1 - 2.98

mg/l

Exposure time: 96 h

Test Method: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential

Components:

acetone:

Partition coefficient: n-

octanol/water

: log Pow: -0.24

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of together with household waste.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container. Do not

dispose of waste into sewer.

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best

practice. Consult state, local or provincial authorities for more

restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

aircraft)

Packing instruction : 353

(passenger aircraft)

IMDG-Code

UN number : UN 1133 Proper shipping name : ADHESIVES

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1133 Proper shipping name : Adhesives

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.



PARABOND® M-163

Version 1.0 Revision Date 03/14/2025

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

n-hexane 110-54-3 Toluene 108-88-3

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR

61):

n-hexane 110-54-3 Toluene 108-88-3

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA All substances listed as active on the TSCA inventory
DSL All components of this product are on the Canadian DSL
TECI On the inventory, or in compliance with the inventory

Please reach out to TEC Speciality Products, LLC for further information regarding chemical inventories not listed above. **Inventories Legend**TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines),

IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION




PARABOND® M-163

Version 1.0

Revision Date 03/14/2025

Further information



Special hazard

HMIS III:

HEALTH	3*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the TEC Specialty Products, LLC from its suppliers, and because the TEC Specialty Products, LLC has no control over the conditions of handling and use, the TEC Specialty Products, LLC makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the TEC Specialty Products, LLC assumes no responsibility for use or reliance thereon. It is the responsibility of the user of TEC Specialty Products, LLC to comply with all applicable federal, state and local laws and regulations.