

PARABOND® M-4259

Version 1.0 Revision Date 03/14/2025

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : PARABOND® M-4259

Product code : 100000012030

Manufacturer or supplier's details

Company : TEC Specialty Products

Address : 1105 South Frontenac

Aurora, IL, 60504

Telephone : 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-800-424-9300

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	viscous liquid	
Color	tan	
Odor	characteristic	

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Potential Health Effects

Carcinogenicity:

IARC Group 1: Carcinogenic to humans During normal handling of the

product, this substance is encapsulated within the product and

will not present a cancer exposure risk. Quartz (SiO2) 14808-60-7

Group 2B: Possibly carcinogenic to humans During normal handling of the product, this substance is encapsulated within the product



PARABOND® M-4259

Version 1.0 Revision Date 03/14/2025

and will not present a cancer exposure risk. Titanium dioxide 13463-67-7

Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Calcium carbonate	471-34-1	10 - 20
kaolin	1332-58-7	10 - 20
Quartz (SiO2)	14808-60-7	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

If inhaled : Move to fresh air in case of accidental inhalation of vapors or

decomposition products.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : If conscious, drink plenty of water.

Never give anything by mouth to an unconscious person.

Consult a physician if necessary.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.



PARABOND® M-4259

Version 1.0 Revision Date 03/14/2025

Unsuitable extinguishing

media

: None known.

Hazardous combustion

products

Specific extinguishing

methods

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

: No hazardous combustion products are known

Special protective equipment

for fire-fighters

: Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Environmental precautions : Refer to protective measures listed in sections 7 and 8.

: Prevent product from entering drains.

Should not be released into the environment.

Methods and materials for

containment and cleaning up

: Ventilate the area.

Soak up with inert absorbent material. Shovel into suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Use only with adequate ventilation/personal protection.

Keep container closed when not in use.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in original container.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	



PARABOND® M-4259

Version 1.0

Revision Date 03/14/2025

		exposure)	Permissible	
		exposure)	concentration	
Calcium carbonate	471-34-1	PEL (Total	10 mg/m3	CAL PEL
Calcium carbonate	471-34-1	dust)	_	
		PEL	5 mg/m3	CAL PEL
		(respirable		
		dust fraction)		
		TWA	5 mg/m3	NIOSH REL
		(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
kaolin	1332-58-7	TWA	2 mg/m3	ACGIH
		(Respirable		
		particulate		
		matter)		
		TWA (total	15 mg/m3	OSHA Z-1
		dust)		
		TWA	5 mg/m3	OSHA Z-1
		(respirable		
		fraction)		
		TWA (Total)	10 mg/m3	OSHA P0
		TWA	5 mg/m3	OSHA P0
		(Respirable		
		fraction)		
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA	5 mg/m3	OSHA P0
		(respirable		
		dust fraction)		
Distillates (petroleum),	64742-52-5	TWA	5 mg/m3	ACGIH
hydrotreated heavy naphthenic		(Inhalable		
		particulate		
		matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL
		(particulate)		
Distillates (petroleum), solvent-	64741-96-4	TWA	5 mg/m3	ACGIH
refined heavy naphthenic		(Inhalable		
		particulate		
		matter)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL	5 mg/m3	CAL PEL
		(particulate)		
Titanium dioxide	13463-67-7	TWA	10 mg/m3	ACGIH



PARABOND® M-4259

Version 1.0

Revision Date 03/14/2025

		TWA (total	15 mg/m3	OSHA Z-1
		dust) TWA (Total)	10 mg/m3	OSHA P0
		TWA (Total)	10 mg/m3	OSHA P0
		dust)	10 1119/1110	OOHATO
		TWA (Respirable particulate matter)	0.2 mg/m3	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m3	ACGIH
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
During a grand based line of A		TWA (respirable dust fraction)	0.1 mg/m3	OSHA PO

During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

not present a cancer exp	i i	1	1	1
Calcium carbonate	471-34-1	PEL (Total	10 mg/m3	CAL PEL
		dust)	· ·	
		PEL	5 mg/m3	CAL PEL
		(respirable		
		dust fraction)		
		TWA	5 mg/m3	NIOSH REL
		(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
kaolin	1332-58-7	TWA	2 mg/m3	ACGIH
		(Respirable	J	
		particulate		
		matter)		
		TWA (total	15 mg/m3	OSHA Z-1



PARABOND® M-4259

Version 1.0 Revision Date 03/14/2025

1		dust)		1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total)	10 mg/m3	OSHA P0
		TWA (Respirable fraction)	5 mg/m3	OSHA P0
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate risk management

measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within

recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields



PARABOND® M-4259

Version 1.0 Revision Date 03/14/2025

Skin and body protection : Skin should be washed after contact.

Protective measures : Avoid contact with skin.

Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : tan

Odor : characteristic
Odor Threshold : no data available

pH : 9.8 - 10.2

is not determined

: is not determined

: is not determined

Flash point : is not determined
Evaporation rate : is not determined
Upper explosion limit : Upper flammability limit

is not determined

Lower explosion limit : Lower flammability limit

is not determined

Vapor pressure : is not determined

Density : 9.3 - 9.8 lb/gal

Solubility(ies)

Water solubility : is not determined
Partition coefficient: n- : no data available

octanol/water

Autoignition temperature : is not determined

Viscosity

Viscosity, kinematic : is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : The product is chemically stable.

Hazardous decomposition

products

: No decomposition if stored and applied as directed.



PARABOND® M-4259

Version 1.0

Revision Date 03/14/2025

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Mobility in soil

No data available

Other adverse effects



PARABOND® M-4259

Version 1.0 Revision Date 03/14/2025

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of together with household waste.

The hazard and precautionary statements displayed on the label also apply to any residues left in the container. Do not

dispose of waste into sewer.

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best

practice. Consult state, local or provincial authorities for more

restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.



PAR	ARC	ND®	M-4259
FAI	ADL		IVI-4ZJJ

Version 1.0

Revision Date 03/14/2025

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

US State Regulations

California Prop 65

Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA DSL


All substances listed as active on the TSCA inventory
All components of this product are on the Canadian DSL

Please reach out to TEC Speciality Products, LLC for further information regarding chemical inventories not listed above. **Inventories Legend**TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	0/
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the TEC Specialty Products, LLC from its suppliers, and because the TEC Specialty Products, LLC has no control over the conditions of handling and use, the TEC Specialty Products, LLC makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from



PARABOND® M-4259

Version 1.0

Revision Date 03/14/2025

the use thereof. The information is supplied solely for your information and consideration, and the TEC Specialty Products, LLC assumes no responsibility for use or reliance thereon. It is the responsibility of the user of TEC Specialty Products, LLC to comply with all applicable federal, state and local laws and regulations.