



Millennium Series 4011

Easy Moisture Control Adhesive



EMC (Easy Moisture Control) 4011 is a premium one-part moisture cure urethane adhesive and moisture control system in a single product that reduces installation labor up to half. EMC 4011 provides both adhesion and moisture protection when applied with the patented specially designed trowel provided with each pail.

- Controls Sub-floor MVER
- One-Step Application, Saves A Day of Labor
- New Trowel With Each Pail
- Excellent Coverage, 215-225 sq. ft. 5 gal.
- Low Odor
- Low VOC, LEED Compliant





Millennium Series 4011

Easy Moisture Control Adhesive

EMC 4011 can be used for glue-down installations of solid, engineered, acrylic impregnated, and parquet wood flooring recommended by the wood flooring manufacturer for glue-down applications. For New Construction concrete applications no moisture testing is required. Sub-floor must be dry to the touch with no standing water or visible dampness.

RECOMMENDED SUBSTRATES:

- Concrete
- Portland Based Underlayments
- Properly Prepared Gypsum
- APA Approved Plywood
- Terrazzo
- Fiber Cement Underlayment
- Radiant Heated Subfloors

TECHNICAL DATA

Base	Urethane
Color	Light Brown
VOC Content	<20 grams per liter
pH	N/A
Coverage	40-45 sf/gallon
Consistency	Creamy Paste
Trowelability	Smooth
Shelf Life	One Year in Unopened Container
Storage	40°-95°F (4.4°-35°C) in a cool, dry location
Application Temperature	65°-95°F (18°-35°C)
Traffic Restrictions	Foot Traffic after 8 hours, Heavy Traffic after 24 hours
Open Time	Up to 45 minutes, depending on ambient conditions
Freeze/Thaw Stability	Store Above 40°F (4.4°C)
Tensile Strength ASTM D 412	350-475 psi
Elongation ASTM D 412	>20%
Tear Strength ASTM D 624	70-85 pli
Full Cure Hardness ASTM D 2240	75-90 Shore A

parabond.com

